

Modelle	Tiefe (C) mm	Höhe (B) mm	Achsenabstand (A) mm	Breite (D) mm	Diameter (Zoll)	Wasserinhalt (L/Glied)	Leistung W/Glied (ΔT 30K)	Leistung W/Glied (ΔT 50K)	Exponent n	Koeffizient (Km)
435	90	484	435	50	G1	0,85	25,6	49,4	1,2849	0,3243
500	90	549	500	50	G1	0,95	28,5	55,1	1,2885	0,3566
535	90	584	535	50	G1	1	30,1	58,2	1,2905	0,3734
600	90	649	600	50	G1	1,10	32,9	63,8	1,2942	0,4037
685	90	734	685	50	G1	1,15	36,6	71,2	1,2990	0,4418
700	90	749	700	50	G1	1,18	37,3	72,5	1,2999	0,4484
800	90	849	800	50	G1	1,34	41,6	81,1	1,3055	0,4907
835	90	884	835	50	G1	1,38	43,1	84,1	1,3075	0,5050
900	90	949	900	50	G1	1,50	45,9	89,7	1,3091	0,5353
935	90	984	935	50	G1	1,56	47,5	92,7	1,3100	0,5514
1000	90	1049	1000	50	G1	1,66	50,3	98,3	1,3115	0,5812
1135	90	1184	1135	50	G1	1,88	56,2	110	1,3149	0,6420
1200	90	1249	1200	50	G1	1,98	59,9	115,7	1,3164	0,6809
1400	90	1449	1400	50	G1	2,28	67,9	133,3	1,3213	0,7583
1435	90	1484	1435	50	G1	2,36	69,5	136,4	1,3210	0,7771
1600	90	1649	1600	50	G1	2,60	77,1	151,2	1,3192	0,8673
1735	90	1784	1735	50	G1	2,85	83,4	163,4	1,3178	0,9430
1800	90	1849	1800	50	G1	2,95	86,4	169,4	1,3171	0,9801
1935	90	1984	1935	50	G1	3,10	92,9	181,9	1,3156	1,0585
2000	90	2049	2000	50	G1	3,22	96,1	188,1	1,3150	1,0970
235	90	284	235	50	G1	0,43	16	30,6	1,2665	0,2158
335	90	384	335	50	G1	0,58	21,1	40,5	1,2792	0,2718
350	90	399	350	50	G1	0,71	21,8	41,9	1,2800	0,2799